

TECHNICAL SPECIFICATIONS

	<i>SUPER QUALITY</i>
<i>Manufacturing Type</i>	Wall to wall (Contract) Special Masjid and Mosque Carpet
<i>Quality System Certifications</i>	DQS EN ISO 9001:2015, DQS EN ISO 14001:2015 and DQS 45001:2015
<i>Construction</i>	Design on the back 2 shot, Wilton Type incorporated (Face to face)
<i>Pile Fiber Content</i>	Domestic Pure New Wool
<i>Pile Quality</i>	100% Pure New Wool. Anti-felting. No composition with skin wool, scrap (waste) wool and nylon.
<i>Surface Protection</i>	“THERMOPRESS” steam treatment to minimize surface deformation.
<i>Cleaning</i>	Carpet yarn is washed according to hygienic standards to remove oil and dirt. Do not emit bad odor.
<i>Warranty</i>	2 (Two) Years
<i>Lifetime Approx</i>	30 Years
<i>Total Weight</i>	4500 gr./m ² (± % 5)
<i>Total Height</i>	16 mm. (± % 5)
<i>Pile Points Sq/ m²</i>	345.600
	When it's requirements we can produce (4000gr 320.000 Points / m ²) and (5000gr 384.000 Points / m ²) these quality
<i>Pile Density</i>	0,166 gr / cm ³
<i>Weft and Warp Material</i>	Weft, %100 Super Quality Jut Warp, 65/35 Polyester/Cotton(NE 12 Extra-Ring)
<i>Backing</i>	Latex. (Vinyl-Acrylic Copolymer) VAC film is coated with 700 gr./ m ² .
<i>Mothproof</i>	Treated with Langsess Eulan substance against moth and insect damage. Life-long full moth protection.
<i>Flammability</i>	It meets the requirements of Bfl-S1 Flammability as per European Norm EN-13501-1 of Germany-Aachen University Textiles and Flooring Institute
<i>UNDERLAY CHARACTERISTIC</i>	
<i>Mixed Underlay</i>	Mixed Underlay Thickness: 4-5mm 1000gr/ m ² Material: Part of a mixed yarn and fabric